

i2u.ai: The Architecture of the Parallel Graph

A Comprehensive Framework for a Decentralized Professional Complementor

1. Strategic Foundation: The Complementor Paradigm

The contemporary digital professional landscape is defined by a paradox of connectivity and isolation. While hyper-connectivity exists through centralized platforms like LinkedIn, the utility of these connections is increasingly diluted by algorithmic interference, rent-seeking monetization strategies, and the commodification of professional identity. The user mandate for **i2u.ai** establishes a critical strategic divergence from the status quo: rather than attempting to displace the incumbent through direct competition—a "substitute" strategy that historically fails due to insurmountable network effects—i2u.ai is positioned as a **complementor**. This report articulates the architectural, technical, and governance mechanisms required to construct this "Parallel Graph," a decentralized overlay that restores professional utility, ensures democratic governance, and facilitates the seamless distribution of high-signal content without disrupting the external web.

1.1 The Economics of the Platform Complementor

A platform complementor creates value that accrues to the base platform's users while capturing a distinct layer of utility that the incumbent cannot or will not provide. In the context of LinkedIn, the "Link Tax" represents the primary market failure i2u.ai addresses. Centralized social media algorithms systematically downrank posts containing external links to retain user attention and ad inventory.¹ This creates a misalignment between the creator's incentive (distribution of knowledge hosted on blogs, newsletters, or repositories) and the platform's incentive (retention).

By architecting i2u.ai as a destination specifically for the *curation and contextualization* of external links, the platform inverts this dynamic. The value proposition shifts from "stay here and scroll" to "find verified professional context here, then read deeply elsewhere." This is validated by the comparative analysis of **Hacker News (HN)** and **Product Hunt (PH)**. While Product Hunt has evolved into a "hivemind" of performative launches where products are built to satisfy the specific tastes of the platform's influencers², Hacker News maintains a focus on intellectual curiosity and technical rigor. Data indicates that while HN may drive lower raw traffic volumes for certain consumer apps compared to PH's gamified environment, it often drives higher quality engagement and conversion for technical and professional tools.³

For i2u.ai, this suggests that the "Parallel Graph" must be anchored in **high-signal utility**

rather than **gamified engagement**. The platform must avoid the "Product of the Day" trap, where visibility is a function of coordinated upvoting, and instead emulate the "contextual relevance" model, where visibility is a function of professional consensus. This distinction is critical for a professional network where reputation is the primary currency. If i2u.ai becomes a "launchpad" for self-promotion, it fails as a complementor. It must instead be a "repository" of verified professional intent.

1.2 The Parallel Graph Architecture

The "Parallel Graph" is the core structural innovation of i2u.ai. It operates alongside the traditional social graph but is topologically distinct.

- **The Primary Graph (LinkedIn):** Nodes are entities (People, Companies) connected by static edges (Employment, Connection). This graph represents *Status*.
- **The Parallel Graph (i2u.ai):** Nodes are **Information Objects** (URLs, Articles, Code Repositories) connected to **Decentralized Identities (DIDs)** through dynamic edges (Endorsements, Contextual Comments, Bridging Votes). This graph represents *Knowledge*.

The non-intrusive nature of this strategy is paramount. The system must not rely on injecting scripts into third-party websites, which introduces security vulnerabilities, privacy concerns, and reliance on the very external sites we aim to respect. Instead, the "overlay" is achieved through a **client-side architecture** (browser extensions, mobile share sheets) that detects the user's presence on a known URL and passively offers the availability of professional context. This creates a "Meta-Layer" over the open web: the user browses the New York Times or a GitHub repo natively, but i2u.ai provides the professional commentary track in a side panel, completely decoupled from the host site's infrastructure.

This architecture ensures resilience. Even if the host site disables comments or goes offline, the professional context within i2u.ai persists. This decoupling of "Content Hosting" (the external web) from "Context Hosting" (i2u.ai) is the definition of a robust parallel graph.

2. Protocol Architecture: The Open-Source Foundation

The choice of underlying protocol dictates the capabilities, governance, and long-term viability of the network. We have evaluated **ActivityPub** and the **AT Protocol** (Authenticated Transfer Protocol) against the specific requirements of professional utility, portability, and customizability.

2.1 The Case for the AT Protocol over ActivityPub

While ActivityPub (powering Mastodon) enjoys a head start in adoption, its architecture presents significant structural impediments to a professional network that requires democratic governance and algorithmic choice.

ActivityPub's Federation Model relies on a server-centric identity (@user@instance.com). This binds the user's identity and social graph to the goodwill and uptime of a specific server administrator. In a professional context, this introduces unacceptable "Server Risk." If a server is defederated or shuts down, the professional's reputation—years of posts and connections—can be effectively erased or severed from the wider network. Furthermore, ActivityPub's content addressing is tightly coupled to the hosting instance, making true "account portability" essentially a myth; usually, only followers can be migrated, not content archives.⁵

The AT Protocol, conversely, employs a user-centric identity model based on **Decentralized Identifiers (DIDs)**. A user's identity (did:plc:123...) is independent of their hosting provider (PDS - Personal Data Server). This allows for **true portability**: a user can migrate their entire repository (posts, likes, graph) from one PDS to another without breaking links or losing their identity.⁷ This provides the "business continuity" assurance required for professional use cases.

Crucially, the AT Protocol separates **Speech** (PDS) from **Reach** (AppView).⁹

- **Speech Layer**: The user's PDS hosts their data. This is the "sovereign" layer.
- **Reach Layer**: Indexing services (AppViews) aggregate data from across the network to build feeds and views.

For i2u.ai, this separation is the "killer feature." It allows us to build a **Specialized Professional AppView** that indexes the global AT Protocol firehose but applies specific filters: "Show me only posts containing links to academic papers, endorsed by users with verified 'Data Scientist' credentials." This custom curation is technically difficult in ActivityPub without forking the entire server software, but it is the native design pattern of the AT Protocol via **Feed Generators**.¹⁰

2.2 Designing the i2u Lexicons

To support "native posts, articles, reactions, and connections" that excel beyond generic microblogging, i2u.ai must define custom **Lexicons** (schemas) within the AT Protocol ecosystem. The standard app.bsky lexicon is insufficient for professional depth. We propose a new namespace, com.i2u, to handle high-fidelity professional data.

Table 1: Proposed i2u Lexicon Definitions

Lexicon ID	Purpose	Key Fields	Professional Utility
com.i2u.feed.article	Long-form native content	title, summary, content	Enables publishing of whitepapers and

		(Markdown/RichText), canonicalUrl (for cross-posting), citations (array of Links)	deep analysis directly on the graph, anchored to external citations.
com.i2u.graph.endorsement	Professional validation	subject (DID), skill (String), strength (1-5), context (URL/Post CID)	Replaces the gamified "Endorsements" of LinkedIn with <i>contextual</i> validation (e.g., "Endorsed for Python based on <i>this</i> code review").
com.i2u.feed.reaction	Nuanced engagement	subject (CID), type (Enum: Insightful, Rigorous, Misleading, Hiring), weight (Float)	Allows for "weighted" sentiment analysis rather than binary "Likes," feeding into the governance engine.
com.i2u.identity.verification	Identity assertions	provider (DID of Verifier), claim (e.g., "Employee"), entity (LEI/Domain), expiry	Cryptographic proof of employment or certification, verifiable by third-party Labelers.

This Lexicon-based approach ensures interoperability. A generic Bluesky client will see an i2u post and falls back to displaying the text summary, while the i2u.ai client (and extension) renders the full rich-text article and professional metadata.¹²

2.3 Integration with the "Fediverse" (ActivityPub)

While AT Protocol is the primary engine, i2u.ai should maintain a "Bridge" to ActivityPub to maximize reach. The ActivityPub standard does support an Article object type¹⁴, which is often underutilized by Mastodon (which treats everything as a Note). i2u.ai can act as a

Protocol Bridge, translating com.i2u.feed.article records into ActivityStreams 2.0 Article objects for federation with Lemmy, Wordpress, and other ActivityPub-compliant platforms. This ensures that a professional's content is visible across the entire decentralized web, satisfying the "open-source architectures" requirement comprehensively.

3. Democratic Governance: The Bridging-Based Ranking Engine

The requirement for "democratic governance" in a professional context implies a system that resists manipulation, polarization, and "lowest-common-denominator" virality. The current industry standard for decentralized, high-signal moderation is **Bridging-Based Ranking**, pioneered by X's Community Notes (formerly Birdwatch).

3.1 The Algorithmic Theory

Traditional engagement algorithms (like LinkedIn's) optimize for probability of interaction ($P(\text{click})$). This inherently favors polarizing or sensational content. Bridging algorithms optimize for **consensus across diverse clusters**. The core hypothesis is that if two groups of users who typically disagree (e.g., "Crypto Optimists" and "Financial Regulators") both find a specific piece of context "Helpful," that context is likely to be objectively true and high-quality.¹⁶

The mathematical foundation relies on **Matrix Factorization** of the User-Rating matrix. The algorithm models the rating r_{ui} (User u rating Note i) as:

$$r_{ui} = \mu + i_u + i_n + f_u \cdot f_n$$

Where:

- μ is the global intercept.
- i_u is the user intercept (how likely the user is to rate *any* note helpful).
- i_n is the note intercept (the intrinsic "helpfulness" of the note).
- f_u and f_n are latent factors representing the user's and note's position in the ideological/professional space.¹⁸

The critical innovation is that the "Helpfulness Score" is derived primarily from i_n , but the model is trained to explain away ratings that are merely the result of alignment ($f_u \cdot f_n$). A note only achieves a high i_n if it receives helpful ratings from users with *opposing* f_u vectors.

3.2 Implementation for Professional Context

i2u.ai will implement this algorithm (open-sourced in Python/C++¹⁹) but adapt the latent factors to represent **Professional Clusters** rather than political tribes.

- **Cluster Detection:** The system naturally identifies clusters based on voting behavior

(e.g., "React Developers," "Embedded Systems Engineers," "Recruiters").

- **Bridging:**
 - A post titled "Why Rust is the Future" might get high ratings from the Rust cluster. This is expected alignment ($f_u \cdot f_n$) and does not trigger a high bridging score.
 - If that same post receives "Insightful" ratings from the "C++ Legacy" cluster, the algorithm detects a "Bridge." The content is then elevated globally as a high-signal professional resource.

This system provides **Democratic Governance** because the "truth" is not determined by a central moderator, but by the emergent consensus of the network. It inherently penalizes "Engagement Pods" (groups of users who blindly like each other's content) because they form a tight, isolated cluster with no bridging connections to the rest of the graph.²¹

3.3 The "Labeler" Ecosystem

The AT Protocol's **Labeler** architecture allows i2u.ai to expose these governance signals as composable layers.²²

- **The Global Bridge Labeler:** The default i2u labeler, emitting i2u:consensus-high labels based on the bridging algorithm.
- **Domain-Specific Labelers:** A "Medical Board" labeler could assert medical:verified on posts linking to clinical trials.
- **User Sovereignty:** Users can subscribe to the labelers they trust. A user might subscribe to the "Global Bridge" for general feed ranking, but also to a specific "Java Champions" labeler to filter their Java content. This decentralizes moderation power away from the platform and back to the professional communities themselves.

4. The Content Engine: Semantic Vectorization & Link2Vec

To "excel in native posts... and connections" while focusing on external links, i2u.ai needs a way to understand the content of those links. The solution is a "**Link-to-Vector**" (**Link2Vec**) engine that transforms URLs into semantic embeddings.

4.1 The Link2Vec Pipeline

This system allows i2u.ai to rank and recommend content based on **Informational Density** and **Semantic Relevance** rather than just keywords or clicks.

1. **Ingestion & Privacy Proxy:** When a user posts a URL, the i2u client (or extension) sends a request to a privacy-preserving proxy. This proxy fetches the oEmbed data, Open Graph tags, and the main text body (using a readability parser).²⁴ This ensures the user's IP is not leaked to the target site during the preview generation.
2. **Semantic Embedding:** The extracted text is passed through an open-source Transformer model. We recommend **Mistral 7B** or **All-MiniLM-L6-v2**²⁶ running on i2u's

inference infrastructure.

- **Output:** A 384-dimensional vector representing the *meaning* of the content.
- 3. **Informational Density Scoring:** Alongside the semantic vector, an NLP pipeline analyzes the text for "Informational Density".²⁸
 - **Metrics:** Unique Entity Count (NER), Citation Frequency, lexical diversity, and absence of "Hype/Buzzwords" (using a custom stop-list of marketing jargon).³⁰
 - **Result:** A scalar score (\$0.0 - 1.0\$) indicating the "Professional Rigor" of the link.

4.2 Application: The "Parallel" Feed

The user's feed is constructed using a hybrid ranking function:

$$\text{Score} = \alpha(\text{UserInterest}) \cdot \text{LinkVector} + \beta(\text{BridgingScore}) + \gamma(\text{DensityScore})$$

This ensures that:

- Users see content relevant to their actual reading history (Vector Similarity).
- High-consensus content floats to the top (Bridging).
- "Fluff" and clickbait are demoted (Density Score).

This directly addresses the requirement for "professional utility" by filtering out the noise that plagues LinkedIn.

5. Identity & Data Strategy: The Open Corporate Graph

A professional network cannot function without a reliable graph of companies and employment. LinkedIn's "moat" is its proprietary database of companies. i2u.ai will disrupt this by building on **Open Data**.

5.1 The GLEIF Backbone

To avoid the "fake company" problem (where anyone can create a "Microsoft" page), i2u.ai integrates with **GLEIF** (Global Legal Entity Identifier Foundation).

- **The LEI Standard:** Every legal entity has a unique 20-character alphanumeric code (LEI).³²
- **Implementation:** When a user lists their employer, i2u.ai queries the **GLEIF API**.³² The user selects the verified entity (e.g., "NVIDIA Corporation - 549300X4D2G7C92Q3N32").
- **Benefits:** This anchors the decentralized graph in legal reality. It allows for precise mapping of corporate hierarchies (Parent/Child entities) which GLEIF provides openly³², a feature LinkedIn struggles to maintain accurately.

5.2 The Startup Ecosystem (OpenVC)

For early-stage startups that may not yet have an LEI, i2u.ai integrates with **OpenVC**, an open database of startups and investors.³⁴

- **Data Integration:** i2u.ai can ingest OpenVC's dataset to pre-populate "Startup Nodes" in the graph.
- **Verification:** Founders can claim these nodes by proving domain ownership (DNS record or did:web), linking their DID to the startup entity. This creates a trusted environment for fundraising and recruitment, leveraging OpenVC's verified investor data.³⁵

5.3 OpenCorporates & API Management

To augment this, i2u.ai utilizes **OpenCorporates**³⁶ for deeper regulatory data (directors, incorporation status). Given that OpenCorporates has API rate limits for free tiers³⁶, i2u.ai will implement a caching layer and potentially a "Bring Your Own Key" (BYOK) model for enterprise users who need high-volume queries. This aligns with the "Complementor" model—we aggregate open sources to provide a unified professional view.

6. The Non-Intrusive Overlay: Client Experience

The "Parallel Graph" is most powerful when it is invisible until needed. The primary interface for i2u.ai is not just a destination website, but a **Browser Extension**.

6.1 The "Side Panel" Architecture

Modern browsers (Chrome, Edge, Firefox) support a **Side Panel API** that allows extensions to open a persistent UI alongside the main content.³⁷

- **Passive Context:** The extension uses a background service worker to hash the URL of the current tab. It queries i2u.ai's index (using k-anonymity privacy hashing) to check for existing discussions or context.
- **The "Badge":** If professional context exists (e.g., a debate on i2u.ai about the article the user is reading), the extension icon displays a subtle badge count.
- **Active Overlay:** When clicked, the Side Panel opens. It loads the **i2u.ai AppView** for that specific URL.
 - **Features:** Users can read the discussion, post a "Reaction" (Insightful/Misleading), or "Connect" with others who are currently reading or have endorsed this content.
- **Safety:** This approach uses **no content scripts** injected into the page DOM. It respects the host site's integrity and security (CSP), satisfying the requirement to "not affect external sites."

6.2 The "Share-to-Graph" Workflow

The extension also solves the distribution friction.

1. User reads an interesting article.

2. Clicks "Share to i2u."
 3. The extension grabs the local metadata, generates the "Link2Vec" embedding locally (or via proxy), and drafts a `com.i2u.feed.article` post.
 4. The post is signed with the user's DID and published to their PDS.
 5. It immediately appears in the "Parallel Graph" feeds of their peers.
-

7. Monetization & Sustainability

To remain a "Complementor" and not devolve into an extractive platform, i2u.ai's business model must align with utility.

- **Enterprise Verification:** Companies pay to manage their "Official Labeler" (`did:plc:google`). This allows them to issue "Verified Employee" badges to their staff, replacing expensive third-party verification services.
 - **High-Signal Feeds:** Access to the core protocol is free. However, access to highly specialized, algorithmically curated feeds (e.g., "The Top 1% Engineering Management Feed," filtered by verified CTOs) can be a subscription product. This monetizes **Curatorial Labor**, not user data.
 - **Recruitment Protocol:** Instead of selling access to resumes (LinkedIn model), i2u.ai enables a "Paid Inbox." Recruiters must pay a fee (set by the user) to send a DM to a candidate. This aligns incentives: the user gets paid for their attention, and the recruiter signals high intent.
-

8. Implementation Roadmap

Phase 1: The Foundation (Months 1-6)

- **Infrastructure:** Deploy AT Protocol PDS clusters and the BGS (Big Graph Service).
- **Data:** Ingest GLEIF and OpenVC datasets to seed the "Company" and "Startup" graph.
- **Development:** Finalize `com.i2u` Lexicons and the "Link2Vec" embedding model.

Phase 2: The Client Overlay (Months 7-12)

- **Release:** Launch the Browser Extension (Chrome/Edge/Firefox) with Side Panel integration.
- **Governance:** Deploy the "Bridging-Based Ranking" algorithm to the main feed.
- **Feature:** Enable "verified" claims for domains and corporate emails.

Phase 3: The Democratic Ecosystem (Year 1+)

- **Decentralization:** Open the "Labeler" API to third-party professional organizations (IEEE, ACM, etc.).
- **Federation:** Allow enterprises to self-host their PDS nodes while remaining part of the i2u parallel graph.

9. Conclusion

i2u.ai represents a necessary evolution in professional networking. By decoupling **Identity** (DID) from **Hosting** (PDS) via the **AT Protocol**, it eliminates the lock-in of centralized platforms. By employing **Bridging-Based Ranking**, it solves the "echo chamber" and "spam" problems inherent in engagement-driven algorithms. And by deploying a **Parallel Graph** strategy that layers professional context over the open web through non-intrusive overlays, it creates a complementor that enhances the utility of the entire internet.

This architecture does not seek to kill LinkedIn; it seeks to make the "walled garden" irrelevant by building a "limitless garden" of verified knowledge and professional trust outside its walls. The result is a platform that is **Utility-First, Democratically Governed, and Open by Default**.

Table 2: Comparison of Governance Models

Feature	LinkedIn (Centralized)	ActivityPub (Federated)	i2u.ai (Bridging/AT Proto)
Moderation Authority	Corporate Trust & Safety Team	Server Admin (Dictator)	Composable Labelers (User Choice)
Ranking Goal	Engagement / Time on Site	Chronological (Mostly)	Bridging / Consensus (Helpfulness)
Spam Defense	Opaque Filters	Server Blocks / Defederation	Community Notes (Algorithmic Defense)
Verification	Proprietary (Blue Check)	Server-based	Open Data (GLEIF/LEI) & DID
Governance Participation	None (User is Product)	Exit (Change Server)	Voice (Voting & Labeling)

Table 3: Technical Stack for i2u.ai

Component	Technology / Standard	Role
Protocol	AT Protocol (Bluesky)	Identity, Federation, Feed Generation
Schema	Lexicon (com.i2u.*)	Defining professional data types
Identity	DID (did:plc, did:web)	Portable, verifiable user identity
Content Ranking	Link2Vec (Mistral/BERT)	Semantic analysis of external links
Governance	Bridging Algorithm (Python/Matrix Fac.)	Cross-cluster consensus ranking
Corporate Data	GLEIF API / OpenVC	Corporate entity verification & graph
Client	Side Panel API (Browser Ext)	Non-intrusive overlay interface

Works cited

1. LinkedIn pros—where do you actually put your links to avoid getting buried? - Reddit, accessed on January 3, 2026, https://www.reddit.com/r/socialmedia/comments/1jxb8l0/linkedin_proswhere_do_you_actually_put_your_links/
2. Analysis of Product Hunt products from 2014 to 2021 - Hacker News, accessed on January 3, 2026, <https://news.ycombinator.com/item?id=42830478>
3. Hacker News vs Product Hunt: A Launch Story | arun thampi, accessed on January 3, 2026, <https://mclouv.in/2015/08/04/Hacker-News-vs-Product-Hunt-A-Launch-Story.html>
4. Lessons launching a developer tool on Hacker News VS Product Hunt and other channels, accessed on January 3, 2026, <https://medium.com/@baristaGeek/lessons-launching-a-developer-tool-on-hacker-news-vs-product-hunt-and-other-channels-27be8784338b>
5. Nostr, love at first sight | Dries Buytaert, accessed on January 3, 2026, <https://dri.es/nostr-love-at-first-sight>
6. If you have to pick one, do you choose to integrate ActivityPub Or AT Protocol

- into your app? : r/fediverse - Reddit, accessed on January 3, 2026,
https://www.reddit.com/r/fediverse/comments/1h97vxd/if_you_have_to_pick_one_do_you_choose_to/
7. AT Protocol - Wikipedia, accessed on January 3, 2026,
https://en.wikipedia.org/wiki/AT_Protocol
 8. Protocol Overview, accessed on January 3, 2026,
<https://atproto.com/guides/overview>
 9. The AT Protocol - Bluesky Documentation, accessed on January 3, 2026,
<https://docs.bsky.app/docs/advanced-guides/atproto>
 10. bluesky-social/feed-generator: ATProto Feed Generator Starter Kit - GitHub, accessed on January 3, 2026, <https://github.com/bluesky-social/feed-generator>
 11. Custom Feeds | Bluesky, accessed on January 3, 2026,
<https://docs.bsky.app/docs/starter-templates/custom-feeds>
 12. Lexicon - AT Protocol, accessed on January 3, 2026,
<https://atproto.com/specs/lexicon>
 13. Lexicon - AT Protocol, accessed on January 3, 2026,
<https://atproto.com/guides/lexicon>
 14. Resolving the Note vs. Article distinction - ActivityPub - SocialHub, accessed on January 3, 2026,
<https://socialhub.activitypub.rocks/t/resolving-the-note-vs-article-distinction/258>
 15. Modeling a Movie Review in ActivityStreams - ActivityPub - SocialHub, accessed on January 3, 2026,
<https://socialhub.activitypub.rocks/t/modeling-a-movie-review-in-activitystreams/3822>
 16. Understanding the strengths and limitations of community-based responses to misinformation | PNAS, accessed on January 3, 2026,
<https://www.pnas.org/doi/10.1073/pnas.2524004122>
 17. Bridging Systems: Open problems for countering destructive divisiveness across ranking, recommenders, and governance | Knight First Amendment Institute, accessed on January 3, 2026,
<https://knightcolumbia.org/content/bridging-systems>
 18. Community Notes by X - LessWrong, accessed on January 3, 2026,
<https://www.lesswrong.com/posts/sx9wTyCp5kgy8xGac/community-notes-by-x>
 19. Documentation and source code powering Twitter's Community Notes - GitHub, accessed on January 3, 2026, <https://github.com/twitter/communitynotes>
 20. etlundquist/rankfm: Factorization Machines for Recommendation and Ranking Problems with Implicit Feedback Data - GitHub, accessed on January 3, 2026,
<https://github.com/etlundquist/rankfm>
 21. Understanding Community Notes and Bridging-Based Ranking - Jonathan Warden's Blog, accessed on January 3, 2026,
<https://jonathanwarden.com/understanding-community-notes/>
 22. Bluesky's Moderation Architecture, accessed on January 3, 2026,
<https://docs.bsky.app/blog/blueskys-moderation-architecture>
 23. Labels and moderation - Bluesky Documentation, accessed on January 3, 2026,
<https://docs.bsky.app/docs/advanced-guides/moderation>

24. oEmbed, accessed on January 3, 2026, <https://oembed.com/>
25. Meta oEmbed Read Explained: The New Way to Embed Facebook and Instagram Posts, accessed on January 3, 2026, <https://www.bluehost.com/blog/meta-oembed-read-explained/>
26. 15 Best Open Source AI Models & LLMs in 2025 (Tested and Reviewed) - Elephas, accessed on January 3, 2026, <https://elephas.app/blog/best-open-source-ai-models>
27. 6 Must-Know Python Sentiment Analysis Libraries - Netguru, accessed on January 3, 2026, <https://www.netguru.com/blog/python-sentiment-analysis-libraries>
28. Autoencoder-Based Framework to Capture Vocabulary Quality in NLP - arXiv, accessed on January 3, 2026, <https://arxiv.org/html/2503.00209v1>
29. Keyword Density Analysis and Search Intent Mapping Using Python - ThatWare, accessed on January 3, 2026, <https://thatware.co/keyword-density-analysis-using-python/>
30. [2509.24638] Hype or not? Formalizing Automatic Promotional Language Detection in Biomedical Research - arXiv, accessed on January 3, 2026, <https://arxiv.org/abs/2509.24638>
31. Enough with the buzzwords, start-ups urged - Inside Small Business, accessed on January 3, 2026, <https://insidesmallbusiness.com.au/marketing/pr-communications/enough-with-the-buzzwords-start-ups-urged>
32. GLEIF API - LEI Data, accessed on January 3, 2026, <https://www.gleif.org/en/lei-data/gleif-api>
33. LEI Data: Access & Use - GLEIF, accessed on January 3, 2026, <https://www.gleif.org/en/lei-data/access-and-use-lei-data>
34. OpenVC | Find investors for your startup — raise for free., accessed on January 3, 2026, <https://www.openvc.app/>
35. The 12 Best Startup Funding Database Platforms of 2025 - fundediq.co, accessed on January 3, 2026, <https://fundediq.co/startup-funding-database/>
36. tutorials/fetch-and-enrich-data-with-apis/README.md at master - GitHub, accessed on January 3, 2026, <https://github.com/maxharlow/tutorials/blob/master/fetch-and-enrich-data-with-apis/README.md>
37. Extension Download - Social Overlay for Google Chrome, accessed on January 3, 2026, <https://social-overlay.en.softonic.com/chrome/extension>